

# 在庫表

## ① 600V 2PNCT (2種 EP ゴム絶縁 クロロブレンキャブタイヤケーブル)

(1) 屈曲・カーテン用

品名		600V 2PNCT, 600V CUR-2PNCT (シールド無しタイプ)													
サイズ	線心数	1	2	3	4	5	6	7	8	10	12	16	20	24	30
0.75 mm <sup>2</sup>			●	●	●	●	●			●	●		●		
1.25 mm <sup>2</sup>			●	●	●	●	●		●	●	●	●	●		●
2 mm <sup>2</sup>			●	●*	●	●	●		●	●	●	●	●	●	●
3.5 mm <sup>2</sup>			●	●*	●	●	●		●	●	●	●	●	●	●
5.5 mm <sup>2</sup>			●	●	●		●								
8 mm <sup>2</sup>		●	●	●	●		●								
14 mm <sup>2</sup>		●	●	●	●										
22 mm <sup>2</sup>		●	●	●	●										
30 mm <sup>2</sup>				●	●										
38 mm <sup>2</sup>		●	●	●	●										
50 mm <sup>2</sup>															
60 mm <sup>2</sup>		●		●	●										
100 mm <sup>2</sup>		●		●											
150 mm <sup>2</sup>		●													

\* : 3 × 2mm<sup>2</sup> ~ 14mm<sup>2</sup>については、黒、白、緑の線心識別も在庫しています。(品名略号: 600V 2PNCT (G)、規格: SP31-90041)

品名		600V 2PNCT-SB, 600V CUR-2PNCT-SB (一括シールドタイプ)													
サイズ	線心数	1	2	3	4	5	6	7	8	10	12	16	20	24	30
1.25 mm <sup>2</sup>				●		●	●								
2 mm <sup>2</sup>			●	●	●	●	●			●			●		●

(2) キャリアドラム用

品名		600V CAR-2PNCT													
サイズ	線心数	1	2	3	4	5	6	7	8	10	12	16	20	24	30
3.5 mm <sup>2</sup>							●			●	●	●	●	●	●
5.5 mm <sup>2</sup>															
8 mm <sup>2</sup>				●			●								
14 mm <sup>2</sup>				●			●								
22 mm <sup>2</sup>				●			●								
30 mm <sup>2</sup>				●											
38 mm <sup>2</sup>				●											
60 mm <sup>2</sup>				●											

## ② 600V FFCT (200°C耐熱フロフレックスフレキシブルケーブル)

品名	線心数	シールド無しタイプ						一括シールドタイプ				
		600V FFCT 600V FFCTB **						600V FFCT-SB 600V FFCTB-SB **				
サイズ	線心数	2	3	4	6	10	20	2	3	4	6	10
1.25 mm <sup>2</sup>		●										
2 mm <sup>2</sup>		●	●	●	●	●	●	●	●	●	●	●
3.5 mm <sup>2</sup>		●	●	●								

\*\* : ガラステープ+ステンレス編組付きは納期が2週間必要です。

【注】在庫品種について、予告なしに変更することがありますのでご了承願います。